

TECHNICAL DATA SHEET

DOUBLE-SIDED TAPES



CARRIER	Cellulose fiber tissue
LINER	White siliconized paper
COLOR	Clear
ADHESIVE	Acrylic
TOTAL THICKNESS	130 μ m (AFERA 4006-ED.9/79)
ADHESION TO STEEL	450 cN/cm (AFERA 4001-ED.10/87)
HEAT RESISTANCE	200 °C (BT internal metod PS-QUA-14)

BN 20900

MAIN APPLICATIONS AND TIPS FOR CORRECT USAGE

For all splicing, holding and laminating operations in the cardboards and film industry. The tape can be stored for maximum 12 months from the date of production in dry conditions and in its original packaging. The material should be protected from extremes of temperature and direct sunlight. Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position.

FEATURES	ADVANTAGES
High quality adhesive	High initial adhesion
	High temperature resistance
Single air-proof bag	Dust and humidity proof
	Long lasting product

WARRANTY

The technical information and data, recommendations, and other statements provided in this document are based on Boston tapes tests or experience. It will be up to the user matching the product with the working process or surface. Boston tapes will not be, at any rate, hold responsible for not proper use. Warranty is limited to replacement of products Boston tapes prove to be defective and keeps out any other damages.

www.bostontapes.it - sales@bostontapes.it

BOSTON tapes S.p.A.

Company under direction and coordination activity of Novacel S.A.

Sede Legale e Stabilimento : Strada Provinciale Cellole - Piedimonte - 81037 Sessa Aurunca (CE). Telefono: 0823 680211 Fax: 0823 703889

Iscrizione C.C.I.A. (Ce) n° 132712 Reg. Trib. 11772/91

